



Nokia 7362 ISAM DF-8G

The Nokia 7362 Intelligent Services Access Manager (ISAM) Dense Fiber (DF)-8G is a compact, fast-deploy access node that efficiently addresses the need to deploy fiber and delivers cutting-edge gigabit services in the lower user density areas.

Product overview

The Nokia 7362 ISAM DF-8G is a one rack unit (1 RU) optical line terminal (OLT) that supports Gigabit Passive Optical Network (GPON). It supports 2 x 10 GigE uplinks and 8-port GPON downlinks. This feature enables up to 20 Gb/s of uplink capacity and 20 Gb/s of GPON downlink capacity.

Service providers have maximum flexibility for deploying the Nokia 7362 ISAM DF-8G in the central office (CO) (rack mountable), in cabinets, within multi-dwelling units (MDUs), office buildings or remote weather-protected locations. The Nokia 7362 DF-8G is part of the ISAM product family and uses the same software and management system as other products in the portfolio, allowing for different deployment options based on techno-economics, local regulations or services offered.

7362DF-8G mini OLT can benefit the service providers by offering the opportunity of easy and rapid applications of PON services in various deployment scenarios with minimum investments.



Features

- High capacity throughput: up to 40 Gb/s full duplex
- Downlink interfaces: fixed configuration supports 8-port GPON
- Uplink interfaces: 2 x 1/10 Gb/s small form-factor pluggable (SFP) modules
- Pluggable, field-replaceable and low acoustic fan unit
- Field-replaceable dust filter
- Deployed indoor or in cabinets
- Rack mountable in 482.6 mm (19 in) racks, 584.2 mm (23 in) or standard 600 mm (23.6 in) ETSI rack



Benefits

- High-bandwidth capacity to meet the demand now and in the future
- Supports GPON including ITU-T G.984.2 B+(28dB), C+(32dB) and Nokia C++(34dB) link budget over -40C to +85C;
- Small shelf size, compact 1 RU access node that operates as a standalone mini OLT
- Rack mountable in the CO and temperature hardened for outside cabinet deployments
- Different power options
- Fan cooled with low noise fan
- One ISAM family: any technology, any service and any deployment model
- Supports existing practices and proven ISAM Technology

Technical specifications

Product specifications

Full service platform

- Multiservice access support
 - IPTV services
 - Multimedia services
 - High-speed internet access (HSIA)
 - Business access
 - Cell site backhaul support
 - 8-port GPON using 8 dual GPON SFP optics that is fully compliant to ISAM FX

OLT

- Network Termination (NT) support
 - 40 Gb/s switching capacity
 - Link aggregation (LAG)
 - 20 Gb/s uplink capacity
 - SFP+ cages

Management

- Fully managed by the Nokia 5520 Access Management System (AMS)
- Simple Network Management Protocol (SNMP) and command line interface (CLI)-based management system

Eco-sustainability

- Power consumption targets code of conduct (CoC) power consumption limits
- Compliant with the European directive 2002/95/ EC on the restriction of the use of certain hazardous substances (RoHS)
- Product collection and treatment under Nokia responsibility complies with the national laws on product treatment applied at the end of life for wastes from electrical and electronic equipment (WEEE), implementing the European Directive (2002/96/EC)
- Product packaging materials are free from hydrochlorofluorocarbons (HCFCs)
- Plastic product packaging material is marked according to ISO 11469, referring to ISO 1043 (97/129/EEC)

Standard compliance

- Environmental
 - ETS EN 300 019-1-1 storage – Class 1.1, weather-protected, partly temperature-controlled locations



ETS EN 300 019-1-2 transport – Class 2.3,
public transportation

– ETS EN 300 019-1-3 stationary use –
Class 3.3 and Class 3.4

– ETS EN 300 132-2

- Protection
 - ITU-T K.20 enhanced and K.45 basic
- Safety
 - IEC 60950, EN 60950 Class 1, AS/NZS 60950.1
 - EN 60950-1
- EMC
 - ETS EN 300 386 for telecommunications center installation environment
 - ETS ES 201 468
 - EN 55022
- Acoustic noise
 - ETS 300 753

Operating environment

- Temperature: -40°C to 65°C (-40°F to 149°F)
- Relative humidity: 5% to 93%, non-condensing
- Over-temperature sensors and shutdown

Power

- Input
 - AC power: 85 V to 280 V AC, 47 Hz to 63 Hz with battery backup
 - DC power: -36 V DC to -72 V DC using

redundant DC power inputs

Dimensions

- Height: 44 mm (1 RU) (1.7 in)
- Width: 442 mm (17.4 in)
- Depth: 267.5 mm (10.5 in), including optical modules and fan tray handle

Weight

- 4.7kg (10.36 lb)